



# Technical Data Sheet

## Bondloc B7765 PTFE Dry Film

### PRODUCT DESCRIPTION

B7765 is a multi-purpose, food grade PTFE dry film for light lubrication. Non- toxic PTFE dry film for use as a dry anti- stick film or light lubrication of links, pins, chutes and slides etc. Operating in food/ clean environments.

### APPLICATIONS

For dry lubrication of sliding parts, especially where oils, greases and similar agents cause soiling. For metals, plastics and rubber. Film thickness of 10cm allows for use even with the very fine tolerances in precision engineering. Can also be used as separation agent e.g. in the plastic processing industry. For sliding roof and seat rails, door hinges and locks, sliding doors, tilting window mechanisms, window locks, furniture hinges, drawer runners, ball bearings and electrical switches.

### USEFUL NOTES

- Non-soiling
- Anti-friction coating
- For metals, plastics and rubber
- Resistant to water, petrol, oils, alkalis and acids.

### INSTRUCTIONS FOR USE

Spray onto the surface from a distance of 20-30 cm. For more detailed application use the extension tube. For best results on moving parts, apply lightly whilst parts are in motion to ensure an even application. Wipe excess off with a cloth. Drying time 5-10 minutes.

### TECHNICAL FEATURES

Appearance	Colourless, dry film
Base Type	PTFE
Propellant	Hydrocarbon
Solvent	Blend of hydrocarbon and alcohol
Temperature Range	-200°C to 270°C

### STORAGE

Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.

### HEALTH & SAFETY

This technical information sheet does not constitute a Safety Data Sheet (SDS). Before using this product ensure you have read and fully understood this products SDS.

### PACKAGING FORMAT

Aerosol Can.....400ml

Bondloc UK Ltd.  
Units 1 & 2  
Bewdley Business Park  
Bewdley, Worcestershire  
DY12 2TZ, UK

+44 (0) 1299 269 269  
sales@bondloc.co.uk





# Technical Data Sheet

## Bondloc B7765 PTFE Dry Film

### PRODUCT DISCLAIMER

Bondloc offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations. The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bondloc's research only. Since the conditions and methods of use of the products are beyond our control, Bondloc expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein. This TDS is one of several tools that may be used to help you find the product best suited for your needs. It is used at your own risk, and by using it, you are knowingly accepting and assuming any and all risks associated with its use and recommendations. BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR ANY AND ALL LOSS OR DAMAGE OF WHATEVER KIND OR NATURE ARISING FROM OR RELATED TO THE HANDLING OR USE OF BONDLOC'S PRODUCTS. The performance of the product, its shelf life, and application characteristics will depend on many variables, including but not limited to the kind of materials to which the product will be applied, the environment in which the product is stored and/or applied, and the equipment used for the application, among other things. Any change in any of these variables can affect the product's performance. You are responsible to test the suitability of any product in advance for any intended use or application. Bondloc does not guarantee the reliability, completeness, use, or function of the statements, technical information, data, and recommendations contained in this TDS.

---

Bondloc UK Ltd.  
Units 1 & 2  
Bewdley Business Park  
Bewdley, Worcestershire  
DY12 2TZ, UK

---

+44 (0) 1299 269 269  
sales@bondloc.co.uk

---

