

Safety Data Sheet Zest-it® Oil Paint Dilutant and Brush Cleaner

According to EC directive 91/155/EEC and subsequent amendments

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Product Name Zest-it® Oil Paint Dilutant and Brush Cleaner

Product Number 25000, 05000, 02500, 01000, 00500, 00250, 00125

Application Thinner for artists oil paint and brush cleaner

Supplier J and T Blackman Ltd. BX2/G036, 90, Sanvey Gate, Leicester. LE1 4BQ

Tel: 0844 8005937. After hours: Tel: 01162341001 Mob. 07885103576

email: msdssupport@zest-it.biz

Container size 50 ml to 25 litre

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	Einecs No.	Cas-No.	Content	Health (class)	Risk (class)
Aliphatic Hydrocarbon	265-149-8	64742-47-8	70 - 90%	Xn	R65. R66.
Orange Terpenes	232-433-8	8028-48-6	10 - 20%	Xn	R65. R10.
Comments	Proprietary preparation of Citrus oils and Hydrocarbon (Benzene <0.1%)				

The Full Text for all R-Phrases are displayed in Section 16

3 HAZARDS IDENTIFICATION

This product is classified as harmful under CHIP(3) Reg.

Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

4 FIRST AID MEASURES

GENERAL INFORMATION In all cases of doubt or when symptoms persist, seek medical

attention. NEVER give anything by mouth to an unconscious

person.

INHALATION If fluid aspirated into lungs. Get medical attention immediately.

Remove person to fresh air. Keep warm and at rest.

INGESTION DO NOT induce vomiting. If vomiting occurs, keep head low so the

stomach content doesn't get into the lungs. Drink plenty of water or milk. Seek medical attention immediately. Provide rest, warmth and

fresh air.

SKIN CONTACT Remove any soaked or contaminated clothing and shoes. Wipe skin

Wash the skin immediately with soap and water. Do not allow saturated clothing to remain in contact with skin for prolonged

periods.

According to EC directive 91/155/EEC and subsequent amendments

EYE CONTACT Remove any contact lenses before rinsing. Promptly flush eyes with

plenty of water while lifting the eyelids. Continue to rinse for up to

15 minutes. If irritation occurs seek medical attention.

5 FIRE FIGHTING MEASURES

GENERAL INFORMATION Classification: non-flammable. Flash point: 67°C (153°F). Auto

ignition: 180°C (356°F). Insoluble in water.

EXTINGUISHING MEDIA Extinguish with foam, carbon dioxide (CO2), dry powder, soil or

water fog. DO NOT use water jet as this will tend to spread the

fire.

SPECIAL FIRE FIGHTING

PROCEDURES

Suitable self contained breathing apparatus should be used in

confined areas. Keep run-off water from fire fighting out of

sewers and water courses.

UNUSUAL FIRE & EXPLOSION

HAZARDS

May produce dense black smoke. Stay up wind of fire. Vapours

are heavier than air and may travel along the ground to nearby

sources of ignition.

SPECIFIC HAZARDS Burning product will liberate carbon dioxide (CO2) and possibly

carbon monoxide (CO). Avoid breathing the smoke.

6 ACCIDENTAL RELEASE MEASURES

GENERAL INFORMATION Ventilate well. Extinguish all sources of ignition. Avoid contact

with eyes and skin. Do not allow to enter sewers or water

courses.

SMALL RELEASE CLEAN UP

METHODS

Contain and absorb with dry sand, soil or oil absorbent

avoiding the use of sawdust. Dispose of as dry oil waste.

LARGE RELEASE CLEAN UP

METHODS

Dike with dry sand, soil or other suitable material, avoiding the

use of sawdust. Recover usable product. Used or

contaminated product should not be allowed to enter sewers or

water courses.

7 HANDLING AND STORAGE

GENERAL INFORMATION Avoid prolonged skin contact. Wash after using.

HANDLING Do not handle or use near open flames or sources of ignition.

STORAGE Store in closed container in a cool well ventilated place away

from sources of ignition.

According to EC directive 91/155/EEC and subsequent amendments

8 EXPOSURE AND PERSONAL PROTECTION

Ingredient LT Exp.(8 hours) ST Exp. (10 minutes)

(Workplace Exposure Limit)

Aliphatic Hydrocarbon 1200 mg/m³

Orange Terpenes 800 mg/m³

ENGINEERING No specific ventilation required.

Ensure that any plant used in conjunction with this product

runs within the product's working temperature range.

VENTILATION Adequate natural ventilation will suffice in most instances.

RESPIRATORY None required in normal use.

Avoid generating mists.

EYE PROTECTION None required in normal use.

Wear safety glasses where splashing is probable.

SKIN PROTECTION None required in normal use.

Nitrile gloves are recommended for prolonged use or sensitive

individuals.

HYGIENE Wash hands after use.

9 PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT 180-239°C (356-462°F) (ASTM 1087)

DENSITY (SG) 0.8 g/cm³

VAPOUR DENSITY 4.5 @ 80°C (Air=1)

VISCOSITY 1.97 mm²/S (IP71)

SOLUBILITY IN WATER Insoluble

pH VALUE $6.4 \pm$

FLASH POINT 67°C (152°F) (PMCC)

AUTO IGNITION TEMPERATURE 180°C (356°F) (ASTM E659)

EXPLOSION LIMITS Lel - 0.6% @ 28°C (82°F) Uel - 6.5% @ 28°C (82°F)

DIELECTRIC STRENGTH 50,000 v

APPEARANCE Clear Liquid

ODOUR Citrus

According to EC directive 91/155/EEC and subsequent amendments

10 STABILITY AND REACTIVITY

STABILITY Stabile.

CONDITIONS TO AVOID Open flames and other sources of ignition.

INCOMPATIBILITY Avoid contact with strong oxidizing agents and acids.

HAZARDOUS DECOMPOSITION None expected under normal circumstances.

By combustion: as with any organic material, combustion will liberate Carbon Dioxide (CO²) and possibly Carbon

Monoxide (CO).

HAZARDOUS POLYMERIZATION Does not occur

11 TOXICOLOGICAL INFORMATION

ROUTE OF ENTRY Skin and/or eye contact.

INGESTION Non-toxic. (LD50> 17,759 mg/Kg) (22 ml/Kg)

Small amounts of vomited liquid ingested or aspirated into lungs

may cause bronchopneumonia.

INHALATION Not relevant at normal room temperatures.

EYE Non-irritant. (Draize Eye Irritation: Score 0.0)

SKIN Non-irritant. (Primary Skin Irritation: Index score 0.2)

Prolonged skin contact may aggravate dermatitis in sensitive

individuals and cause skin dryness or cracking.

CARCINOGENICITY

LISTING

NPT - None, IARC - None, OSHA - None, ACGIH - None,

12 ECOLOGICAL INFORMATION

ECOLOGICAL HAZARD None expected.

BIODEGRADATION (EEC) Biodegradable. Liquid will evaporate readily.

DEGRADATION Inherently biodegradable (OECD).

No acute toxicity to aquatic organisms is expected.

BIOACCUMULATION Should not occur.

13 DISPOSAL CONSIDERATIONS

DISPOSAL Not considered a hazardous waste. This product is classified as Inherently

Biodegradable. In its purchased state it may be disposed of as oil waste. Used or contaminated product should be disposed of in accordance with the

contaminate.

According to EC directive 91/155/EEC and subsequent amendments

14 TRANSPORTATION INFORMATION

GENERAL INFORMATION This product is not regulated for transport and is not a marine

pollutant. Intrastate Ref. 2910-10-90

DOT LABELING Not applicable.

PROPER SHIPPING NAME Not applicable.

HAZARD CLASS Not applicable.

UN No. Not applicable.

15 REGULATORY INFORMATION

LABEL RISK PHRASES R-65 Harmful: may cause lung damage if swallowed.

R-66 Repeated exposure may cause skin dryness or cracking.

LABEL SAFETY

PHRASES

S-62 If swallowed, do not induce vomiting; seek medical

advice immediately and show this container or label.

CONTAINS Citrus oil and Hydrocarbons.

UK REGULATORY

REFERENCE

Chemicals (Hazard Information & Packaging for Supply)

(CHIPS 3)

APPROVED CODE OF

PRACTICE COSHH

Classification and Labelling of Substances and Preparations

Dangerous for Supply.

16 OTHER INFORMATION				
DATE	1 Jul 2008			
SHEET REF. No.	Zest-it Brush Cleaner CHIP 3			
PRODUCT COVERED BY THE SHEET	All sizes of Zest-it Oil Paint Dilutant and Brush Cleaner.			
REPLACES SHEET	1 Aug 2002			
RISK PHRASES IN FULL	R-10 Flammable R-65 Harmful, may cause lung damage if swallowed. R-66 Repeated exposure may cause skin dryness or cracking.			

Disclaimer. The information contained in this document is furnished without warranty of any kind. Users should consider this data only as a supplement to other information gathered by themselves and must make independent determinations of the suitability and completeness of information from all sources to ensure proper use and disposal of these materials and the safety of their employees and customers.