

...the Hoffmann Dovetail Key

MU 3 / MU 3-D Manual Dovetail Routing Machine









Transportable and adaptable bench-top machine, to rout a single dovetail slot with each machine cycle for Hoffmann Keys sizes W-1/-2/-3/-4.

Operation

Position and secure the fence plate and lay the work-piece against it. By drawing down the hand lever, the workpiece is clamped and the motor starts. Continued pressure on the lever raises the router unit through the workpiece and to the pre-set routing depth. When the hand lever is returned to its original position motor switches off automatically and the routed work-piece is released.

On the model version MU 3-D the routing position, as well as the routing depth are digitally displayed to an accuracy of 1/10th mm.



Options



Digital display for:

> fence plate/routing position > routing depth

Ergonomic lever design

...brilliantly simple

Scale with magnifying lense

Routing depth

and lever limiter



Fine motor adjustment

Ergonomic operator bay

simply brilliant...



Fences

Angle fence plate elevation



Butt stop fence



Internal fence





Butt stop fence elevation



Internal fence elevation



Cornice fence









Technical data


Flip stop "Mini"



Digital display for flip stops



Adjustable internal fence



1ph/N/PE 230 V 50/60Hz 1.0 kW Electrical connection Motor 1 x 1000 W Overall sizes B/W/H 740/650/835 Weight 32 kg Order No. W1031000





Centre line location jig



Adjustable fence "Synchro" 0-90°

MU 3-P / MU 3-PD Pneumatic Dovetail Routing Machine



Transportable and adaptable bench-top machine, to rout a single dovetail slot with each machine cycle for Hoffmann Keys sizes W-1/ -2/ -3 /-4.

Operation

Position and secure the fence plate and lay the work-piece against it. By actuating the foot pedal, the work-piece is pneumatically clamped and the motor starts. The router unit rises through the work-piece and to the pre-set routing depth. When the routing depth is reached the unit returns to its home position and switches off. The routed workpiece is then released.



Electrical connection	1ph/N/PE 230 V 50/60Hz 1.0 kW	
Air pressure	6 bar	
Motor	1 x 1000 W	
Rotation speed without load	34000 1/min.	
Control	pneumatic	
Work-piece clamping	pneumatic	
Height capacity	150 mm	
Routing depth	0-95 mm	
Extraction port size	Ø 50 mm	
Hoffmann Key sizes	W-1/2/3/4	
Overall sizes B/W/H	740/650/835	
Weight	32 kg	
Order No.	W1032000	

Machines & Accessories

MU 3 / MU 3-P

Machines

MU 3 Dovetail routing machine manual	W1031000	MU 3-P Dovetail routing machine pneumatic	W1032000

Accessories

W3060000
W3010000
W3012000
W3011000
W3013000
W3014000
W3015000
W3016000
W3017000
W3018000
W3019000

Butt stop fence	W3020000
Cornice fence	W3021000
Flip stop for extension fence	W3022000
Flip stop for rear fence plane	W3023000
Flip stop "Mini"	W3024000
Centre line location jig	W3025000
Multi digital gauge	W3026000
Laser line	W3027000
Routing depth and lever limiter	W3028000
Extension fence, 1000 mm each	W3029000
Mullion fence guide	W3030000
Sliding fence	W3031000



Hoffmann GmbH Maschinenbau

Mergelgrube 5 · D-76646 Bruchsal

Telefon +49 (0) 72 51 - 95 44 0
Telefax +49 (0) 72 51 - 95 44 44
Home www.hoffmann-schwalbe.de
E-Mail info@hoffmann-schwalbe.de



best joints...worldwide!