

PRODUCT DATA

Product Code: WEB5014

Description: WEB5014 is an uncoated white woodfree paper specifically designed for the production of self adhesive ‘display boards’.

Supplied with a lower coat weight of **WM810** peelable acrylic adhesive which offers a ‘clean peel’ low tack adhesion to a wide range of surfaces.

Face Material: 80gsm white woodfree paper.

Substance	80 gsm	ISO 536
Tensile Strength	MD 5.0 kN/m	ISO 1924
	CD 2.5 kN/m	ISO 1924

Adhesive : WM810 is a peelable acrylic emulsion-based adhesive.

Initial tack	150 N/m	FTM 9
Peel adhesion	120 N/m	FTM 1
Application temperature	+5°c	
Service temperature range	-20°c.....+75°c	

Liner: 87gsm siliconised white clay coated kraft .

Substance	87±5	ISO 536
Caliper	95±8	ISO 534
Tensile Strength	MD 4.0 kN/m	ISO 1924
	CD 2.0 kN/m	ISO 1924

All statements, technical information and recommendations about **Webmaster** products are based on tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold on the basis that the purchaser shall make their own tests to determine the suitability of such products for their particular applications and uses, and that the purchaser assumes all risks and liabilities for the results of the use of the products, including use in accordance with the seller’s recommendations. No salesman, representative or agent of **Webmaster** is authorised to give any guarantee, warranty or make any representation contrary to the above.