Page: 1/11



Safety data sheet

according to 830/2015/EC

Printing date: 21.01.2016

Revision: 21.01.2016

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

· Trade name: Varnish Remover

Product code: PC-123

• **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture: Varnish remover

1.3 Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Gainsborough Products, LLC 6680 Alhambra Ave. #249 Martinez, CA 94553-6105 USA (925) 957-9277 service@gainsboroughproducts.com

1.4 Emergency telephone number:

ChemTel Inc. +1 (800)255-3924, +1 (813)248-0585

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

[•] 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation. • Hazard pictograms



· Signal word Danger

Hazard-determining components of labelling: acetone pentyl acetate
Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

(Cont'd. on page 2)



Printing date: 21.01.2016

Revision: 21.01.2016

Trade name: Varnish Remover

(Cont'd. from page 1)

 Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist/vapours/spray. Wear protective gloves/protective clothing/eye protection. P280 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. P312 In case of fire: Use for extinction: CO2, powder or water spray. P370+P378 Store in a well-ventilated place. Keep cool. P403+P235 · Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. 2.3 Other hazards There are no other hazards not otherwise classified that have been identified. · Results of PBT and vPvB assessment · **PBT:** Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

[•] 3.2 Mixtures

· Dangerous components:

Dangerous components.			
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8		 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	90-99%
CAS: 628-63-7 EINECS: 211-047-3 Index number: 607-130-00-2	pentyl acetate	🚸 Flam. Liq. 3, H226	1-5%

· Additional information:

For the listed ingredient(s), the identity and exact percentages are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

SECTION 4: First aid measures

[•] 4.1 Description of first aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately rinse with water.

If skin irritation is experienced, consult a doctor.

(Cont'd. on page 3)



Printing date: 21.01.2016

Revision: 21.01.2016

Trade name: Varnish Remover

(Cont'd. from page 2) • After eve contact: Remove contact lenses if worn, if possible. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately. 4.2 Most important symptoms and effects, both acute and delayed Headache Breathing difficulty Coughing Dizziness Acidosis Irritant to eyes. Slight irritant effect on skin and mucous membranes. Nausea in case of ingestion. Gastric or intestinal disorders when ingested. Vomiting. Diarrhea. Disorientation Unconsciousness · Hazards: Danger of impaired breathing. 4.3 Indication of any immediate medical attention and special treatment needed If necessary oxygen respiration treatment. Medical supervision for at least 48 hours. **SECTION 5: Firefighting measures** 5.1 Extinguishing media Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · For safety reasons unsuitable extinguishing agents: None. 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire. • 5.3 Advice for firefighters · Protective equipment: Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

Use large quantities of foam as it is partially destroyed by the product.

(Cont'd. on page 4)



Page: 4/11

Printing date: 21.01.2016

Trade name: Varnish Remover

(Cont'd. from page 3)

Revision: 21.01.2016

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Protect from heat.

6.2 Environmental precautions

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

6.3 Methods and material for containment and cleaning up

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

[•] 7.1 Precautions for safe handling

Use only in well ventilated areas.

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Rags / metal wools / cuttings / shavings and waste papers soaked with product must be placed in a sealed, metal container rated for flammable waste.

Information about fire - and explosion protection:

Highly flammable liquid and vapour.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Keep respiratory protective device available.

Emergency cooling must be available in case of nearby fire.

Fumes can combine with air to form an explosive mixture.

Flammable gas-air mixtures may form in empty receptacles.

7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame. Provide ventilation for receptacles.

• Information about storage in one common storage facility: Store away from foodstuffs.

Do not store together with oxidising and acidic materials.

• Further information about storage conditions: Keep container tightly sealed.

(Cont'd. on page 5)



Revision: 21.01.2016

(Cont'd. from page 4)

Printing date: 21.01.2016

Trade name: Varnish Remover

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection				
 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 				
IOELV (EU)	Long-term value: 1210 mg/m ³ , 500 ppm			
WEL (Great Britain)	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm			
628-63-7 pentyl ace				
IOELV (EU)	Short-term value: 540 mg/m³, 100 ppm Long-term value: 270 mg/m³, 50 ppm			
, , , , , , , , , , , , , , , , , , ,	Short-term value: 541 mg/m³, 100 ppm Long-term value: 270 mg/m³, 50 ppm			
	relevant information available.			
The usual precaution Keep away from foo Immediately remove Wash hands before Do not inhale gases Avoid close or long t Avoid contact with th Respiratory protec Not required under r Use suitable respirat	e equipment: and hygienic measures: nary measures are to be adhered to when handling chemicals. dstuffs, beverages and feed. e all soiled and contaminated clothing. breaks and at the end of work. / fumes / aerosols. term contact with the skin. he eyes. tion: normal conditions of use. tory protective device in case of insufficient ventilation. tory protective device when aerosol or mist is formed. biratory protection may be advisable.			
Protective g	loves			
 Material of gloves Butyl rubber, BR Fluorocarbon rubber Not suitable are glo Nitrile rubber, NBR 	nas to be impermeable and resistant to the product/ the substance/ the preparation. r (Viton) oves made of the following materials:			
PVC gloves	(Cont'd. on page 6)			



Revision: 21.01.2016

Printing date: 21.01.2016

Trade name: Varnish Remover

(Cont'd. from page 5)

PVA gloves Eye protection:

Safety glasses

· Body protection: Protective work clothing

- · Limitation and supervision of exposure into the environment: Avoid release to the environment.
- · Risk management measures: See Section 7 for additional information.

SECTION 9: Physical and chemical properties				
9.1 Information on basic physical and chemical properties				
Appearance				
Form:	Liquid			
Colour:	Colourless			
Odour:	Fruit-like			
Odour threshold:	Not determined.			
pH-value:	Not determined.			
Melting point/Melting range:	-95,35 °C			
Boiling point/Boiling range:	55-58 °C			
Flash point:	-20 °C (TCC)			
Flammability (solid, gaseous):	Not applicable.			
Auto/Self-ignition temperature:	465 °C			
Decomposition temperature:	Not determined.			
Self-igniting:	Product is not self-igniting.			
Danger of explosion:	Product is not explosive. However, formation of explosive a vapour mixtures are possible.			
Explosion limits				
Lower:	2,5 Vol %			
Upper:	12,8 Vol %			
Vapour pressure at 39,5 °C:	533,29 hPa			
Density at 20 °C:	<1 g/cm ³			
Relative density:	Not determined.			
Vapour density at 20 °C:	>1 g/cm³ (Air = 1)			
Evaporation rate at 20 °C:	<1 (Diethyl ether = 1)			
Solubility in / Miscibility with				
water:	Fully miscible.			
	(Cont'd. on page			

Page: 6/11



Printing date: 21.01.2016

Revision: 21.01.2016

(Cont'd. from page 6)

Trade name: Varnish Remover

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity

Dynamic: Kinematic: 9.2 Other information Not determined. Not determined. No further relevant information available.

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: Keep away from heat and direct sunlight.

10.3 Possibility of hazardous reactions

Highly flammable liquid and vapour.

Reacts violently with oxidising agents.

Reacts with strong acids and alkali.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

10.4 Conditions to avoid Excessive heat.

* 10.5 Incompatible materials Oxidizers, strong bases, strong acids

· 10.6 Hazardous decomposition products Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

• Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

67-64-1 acetone

Oral LD50 5800 mg/kg (rat)

Dermal LD50 20000 mg/kg (rabbit)

Primary irritant effect

· Skin corrosion/irritation: Slight irritant effect on skin and mucous membranes.

· Serious eye damage/irritation:

Causes serious eye irritation.

· Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Probable routes of exposure:

Ingestion. Eye contact.

Inhalation.

(Cont'd. on page 8)



Safety data sheet

according to 830/2015/EC

Revision: 21.01.2016

(Cont'd. from page 7)

Printing date: 21.01.2016

Trade name: Varnish Remover

Skin contact.

- · Acute effects (acute toxicity, irritation and corrosivity): Vapours have narcotic effect.
- Repeated dose toxicity: Repeated exposure may cause skin dryness or cracking.
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure:
- May cause drowsiness or dizziness.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

[·] 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- * **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- . 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

· Recommendation

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

(Cont'd. on page 9)



Printing date: 21.01.2016

Trade name: Varnish Remover

Revision: 21.01.2016

(Cont'd. from page 8)

SECTION 14: Transport information	
[·] 14.1 UN-Number [·] DOT, ADR, IMDG, IATA	UN1263
[·] 14.2 UN proper shipping name	
Limited Quantity for packages less t gal).	han 30 kg (66 lb) and inner packagings less than 5 L (
DOT, IATA ADR IMDG	Paint related material 1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
· DOT	
PLANAGE (RD)	
· Class · Label	3 Flammable liquids.
	3
· Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
 14.4 Packing group DOT, ADR, IMDG, IATA 	II
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user Danger code (Kemler): 	Warning: Flammable liquids. 33
	(Cont'd. on page



Safety data sheet

Printing date: 21.01.2016

according to 830/2015/EC

Revision: 21.01.2016

Trade name: Varnish Remover

(Cont'd. from pag
F-E, <u>S-E</u>
nnex II
Not applicable.
2
D/E
Limited quantity by air: 1L
-

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenic Categories

· IARC (International Agency for Research on Cancer)

None of the ingredients are listed.

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients are listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms: ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)

(Cont'd. on page 11)



Printing date: 21.01.2016

Trade name: Varnish Remover

Revision: 21.01.2016

(Cont'd. from page 10) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 · Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com