

PART NO	DESCRIPTION	SPEC	Q'TY
KD0410	SCREW	#4×10 TP	1
KD0416	SCREW	#4×16 TP	2
KP3016	PARALLEL PIN	φ3×16L	1
KP35165	PARALLEL PIN	φ3.5×16.5L	2
KP4016	PARALLEL PIN	φ4×16L	1
KP5014	PARALLEL PIN	φ5×14L	1
KS3005	SPRING PIN	φ3-5L	1
KS3010	SPRING PIN	φ3-10L	2
KS3012	SPRING PIN	φ3-12L	1
KX0410	CAP HD.BOLT	M4×0.7-10L	2
KX0518	CAP HD.BOLT	M5×0.8-18L	1
KX0522	CAP HD.BOLT	M5×0.8-22L	1
WRH0102	FRONT BODY		1
WRH0202	REAR BODY		1
WRH0301	COMPRESSION SPRING		1
WRH0401	TRIGGER		1
WRH0501	SPRING		1
WRH0602	TONGUE		1
WRH0701	GUIDE PLATE		1
WRH0801	LATCH		1
WRH0901	FRONT PLATE		1
WRH1001	PUSHER STOP		1
WRH1301	PIVOT		1
WRH1401	BUMPER		1
WRH1501	BUMPER		1
WRH1601	SHAFT		1
WRH1701	FRONT HOUSING		1
WRH1801	COMPRESSION SPRING		1
WRH2001	GUIDE STEM		1
WRH2101	SPRING		1
WRH2201	PLATE		1
WRH2301	PUSHER		1
WRH2401	ADJUSTABLE KNOB		1
WRH2701	RUBBER PLATE		1
WRH2801	PUSH ASSY.		1
WRH2901	NUT		1
WRH3001	SCREW		1
WRH3101	SHAFT		1
WRH3201	SHAFT		1
WRH3401	DRIVER SET		1
YE2001	E-RING	φ2.0	1
YN0508A	HEX.NUT	M5×0.8(T=2.7MM)	2
YN0610	HEX.NUT	M6×1.0	1



PUB116

v.1 05/2021

Flexipoint Driver - Manual 10400

Thumb magazine release
for easy front loading of flexis



Comfortable soft handle

Weights 570g,
less than many other drivers

Adjustable
insertion
pressure

Side exit allows slide
and fire for speed

Wide foot for stability

Flexis are inserted almost flush with
back board. No pressing-down needed

Takes LION flexis and most
other 15mm x 4.5mm flexis

